



Following Specifications are all Available for CM-96, CB-96, CA-96, CA-72

D.C. Ammeters

mA	1
	2.5
	5
	10
A	1
	2.5
	6
	10
	25
	40
above 50A with separate external shunt (70mV)	50
	60
	100
	150
	250
	400
	600

D.C. Voltmeters

mV	60
	80
	100
	120
	150
	300
	500
V	10
	15
	25
	40
	60
	100
	150
	250
	400
	600

A.C. Ammeters

A	1
	2.5
	5
	10
Direct	25
	40
	50
	60
	100
	10/5
	15/5
	25/5
	40/5
	60/5
	100/5
	150/5
	250/5
	400/5
	600/5
	1000/5
	1500/5
	2500/5
	4000/5
	6000/5

A.C. Voltmeters

V	100
	150
	300
	500
	600

Pointer Frequency meters

Line supply
110; 220; 380; 440V

Measuring range
45 ~ 55; 45 ~ 65Hz
55 ~ 65Hz

Vibrating Reed Frequency meters

Line supply
110; 220; 380 ; 440V

Frequency spans:
11 Reed: 45 ~ 55 Hz
55 ~ 65 Hz

Power factor meters

3-phase, 3-wire
balanced line*

110V	5A
220V	5A
380V	5A
440V	5A

Wattmeters

3-phase, 3-wire
balanced line*

110V	5A
220V	5A
380V	5A
440V	5A

3-phase,4-wire
unbalanced line*

110v	5A
220v	5A
380v	5A
440v	5A

* Other Specifications upon Request.