



PANEL METER THE INTERCHANGEABLE SCALE

MODEL NO.	MEASUREMENT	MEASUREMENT RANGE	MOVEMENT	SCALES	
CP-96	VOLTMETERS	DC	3, 5, 7.5, 10, 15, 20, 30, 50, 75, 100, 150, 200, 250, 300, 450, 500, 600V	Moving Coil	
CP-72		AC	30, 50, 75, 100, 120, 150, 200, 250, 300, 400, 450, 500, 600V	Moving Iron	
CP-48					
CP-96	FREQUENCYS METER	POINTER TYPE	45~55Hz, 55~65Hz 45 - 65Hz	Moving Coil	90°
CP-72	LINE SUPPLY	REED TYPE	CP-96 11 REED 45-55Hz 55-65Hz		
★CP-48 (POINTER TYPE ONLY)	110V, 220V, 380V, 440V AC		CP-72 7 REED 47-53Hz 57-63Hz		
CW-96	AMMETERS	AC	Direct : 0.1, 0.5, 1, 1.5, 3, 5, 7.5, 10, 15, 20, 30A Above 30A with separate external current transformer which secondary current is 5A	Moving Coil	240°
		DC	Direct : 1,3,5,10,15,20,30,50,75, 100,150,200,250,300,500mA 1,3,5,7.5,10,20,30,50A Above 50A with separate external shunt(50 or 75mv)		
CW-72	VOLTMETERS	DC	3, 5, 7.5, 10, 15, 20, 30, 50, 75, 100, 150, 200, 250, 300, 450, 500, 600V		
		AC	30, 50, 75, 100, 120, 150 200, 250, 300, 400, 450, 500, 600V		
	FREQUENCYS METERS LINE SUPPLY 110V, 220V, 380V 440V AC	POINTER TYPE	45-55Hz 55-65Hz		
CP-96	POWER FACTOR METERS	3 PHASE 3 WIRE BALANCED LINE LINE SUPPLY : 5A L-L : AC 220V, 380V, 415V, 440V	Moving Coil	CP-96 90°	
CP-72				CP-72 90°	
CW-96	WATTMETERS	3 PHASE 4 WIRE (wattmeter only) UNBALANCED LINE LINE SUPPLY : 5A L-N : AC 120V, 220V, 240V		CW-96 240°	
CW-72				CW-72 240°	

★ CP-96 AND CP-72 DOUBLE FREQUENCY METER REED TYPE AVAILABLE.