




## CONTROL UNIT M SERIES

### SELECTOR SWITCHES



### KEYLOCK SWITCH



### MODEL DESIGNATION

TYPE	MOUNTING DIA	OPERATING SYSTEM	CONTACT CONFIGURATION
1. LKOS=Lever Selector 2. SKOS=Knob Selector 3. SKL=Keylock Switch	1. 22=Ø22 2. 25=Ø25 3. 30=Ø30	1. 2=2-notch 2. 3=3-notch	1. 10=1a      7. 30=3a 2. 01=1b      8. 03=3b 3. 11=1a1b    9. 33=3a3b 4. 20=2a      10. 40=4a 5. 02=2b      11. 04=4b 6. 22=2a2b    12. 44=4a4b

### PILOT LIGHT



R	Ø22	CA-22MR	CA-22MG	CA-22MY	CA-22MB	CA-22MW
G	Ø25	CA-25MR	CA-25MG	CA-25MY	CA-25MB	CA-25MW
Y						
B	Ø30	CA-30MR	CA-30MG	CA-30MY	CA-30MB	CA-30MW
W						



ITEM NO.	MOUNTING DIA	COLOR
CA22M-N	Ø22	RED:R YELLOW:Y BLUE:B GREEN:G WHITE:W
CA25M-N	Ø25	
CA30M-N	Ø30	


### PILOT LIGHT

#### TP TYPE



- TRANSFORMER PILOT LIGHT  
ACV : 110,220,380,440V  
E-10 6.3V FILAMENT BULB

#### TP TYPE



ITEM NO.	MOUNTING DIA	COLOR
TP-22M	Ø22	G: GREEN R: RED Y: YELLOW B: BLUE W: WHITE
TP-25M	Ø25	
TP-30M	Ø30	