



TYPE C CONTACTORS & THERMAL OVERLOAD RELAY

PICTURE																			
ITEM NO.		S-C10			S-C11			S-C12			S-C16			S-C21			S-C35		
3 ϕ MOTOR RATING	V	220	380	440	220	380	440	220	380	440	220	380	440	220	380	440	220	380	440
	A	12	9	9	12	9	9	12	9	9	16	12	12	22	20	20	35	32	32
	KW	2.2	4	4	2.2	4	4	2.2	4	4	3.7	5.5	5.5	5.5	11	11	9	15	15
AC-1 & I _m (A)		20			20			20			25			32			50		
NUMBER OF AUX. POLES		1 NO+1 NC			1 NO			1 NO+1 NC			1 NO+1 NC			2 NO+2 NC			2 NO+2 NC		
WEIGHT (kg)		0.25			0.3			0.35			0.35			0.6			1.0		
DIMENSIONS (mm)		 A=40 B=57 C=49 D=30			 A=44 B=62 C=46 D=34			 A=55 B=60 C=45 D=43			 A=55 B=60 C=45 D=43			 A=68 B=74 C=58 D=54			 A=85 B=87 C=73 D=70		
TYPE TH THERMAL OVERLOAD RELAY	TH-12	 0.6A (0.45-0.75) 0.9A (0.7-1.1) 1.2A (0.9-1.5) 1.7A (1.4-2.1) 2.1A (1.6-2.6) 2.8A (2.2-3.4)			3.5A (2.6-4.2) 5A (4-6) 6.5A (5.2-7.8) 9A (7-11) 11A (9-13)			TH-20			 0.6A (0.45-0.75) 0.9A (0.7-1.1) 1.2A (0.9-1.5) 1.7A (1.4-2.1) 2.1A (1.6-2.6) 2.8A (2.2-3.4) 3.5A (2.6-4.2) 5A (4-6) 6.5A (5.2-7.8) 9A (7-11) 11A (9-13) 15A (12-18)			 TH-20T 22A (18-26) 30A (24-36) 35A (28-42)					
	ASSOCIATED CONTACTOR	S-C10, S-C11, S-C12						S-C16, S-C21						S-C35					
WEIGHT (kg)		0.1						0.15						0.2					

Please note—S-C10, S-C11, S-C12, S-C16, S-C21, S-C35 and S-C50 these 7 Items are also DIN RAIL TYPE