




MAGNETIC CONTACTORS


C1-D SERIES AC CONTACTOR



SPECIFICATIONS

ITEM NO		C1-D09	C1-D12	C1-D18	C1-D25	C1-D32	C1-D40	C1-D50	C1-D65	C1-D80	C1-D95	
AC1 DUTY MAX A		25A	25A	32A	40A	50A	60A	80A	90A	125A	130A	
AC3 DUTY 3 PHASE MOTOR RATING	220V	KW	2.2	3	4	5.5	7.5	11	15	18.5	22	25
		HP	3	4	5.5	7.5	10	15	20	25	30	35
	380V	KW	4	5.5	7.5	11	15	18.5	22	30	37	45
		HP	5.5	7.5	10	15	20	25	30	40	50	60
	440V	KW	4	5.5	9	11	15	22	25	37	45	45
		HP	5.5	7.5	12	15	20	30	35	50	60	60
A		9A	12A	18A	25A	32A	40A	50A	65A	80A	95A	
NUMBER OF AUX. POLES		1A or 1B	1A or 1B	1A or 1B	1A or 1B	1A or 1B	1A1B	1A1B	1A1B	1A1B	1A1B	
PACKING: PCS/CARTON		60	60	60	40	40	12	12	12	8	8	

A1-D SERIES AUXILIARY CONTACT GROUP




packing
4pole: 200pcs/c
2pole: 300pcs/c

SPECIFICATIONS

Item No.	A1-D-02	A1-D-11	A1-D-20	A1-D-22	A1-D-40	A1-D-04	A1-D-13	A1-D-31
The number of contact	2NC	NO + NC	2NO	2NO+2NC	4NO	4NC	NO + 3NC	3NO + NC

R1-D SERIES THERMAL OVERLOAD RELAY



packing
R1-D09-25: 100pcs/carton
R1-D40-80: 60pcs/carton

SPECIFICATIONS

ITEM NO.	Adjusting range of current (A)	Control power (AC3) (KW)					Plug in contactor
		220V	380V	415V	440V	660V	
R1-D-09301	0.1 ~ 0.16						C1-D09-32
R1-D-09302	0.16 ~ 0.25						C1-D09-32
R1-D-09303	0.25 ~ 0.40						C1-D09-32
R1-D-09304	0.40 ~ 0.63					0.37	C1-D09-32
R1-D-09305	0.63 ~ 1					0.55	C1-D09-32
R1-D-09306	1 ~ 1.6		0.37		0.55	0.7 ~ 1.1	C1-D09-32
R1-D-09307	1.6 ~ 2.5	0.37	0.55 ~ 0.75	1.1	0.75 ~ 1.1	1.5	C1-D09-32
R1-D-09308	2.5 ~ 4	0.55 ~ 0.75	1.1 ~ 1.5	1.5	1.5	2.2 ~ 3	C1-D09-32
R1-D-09310	4 ~ 6	1.1	2.2	2.2	2.2	4	C1-D09-32
R1-D-09312	5.5 ~ 8	1.5	3	3 ~ 3.7	3 ~ 3.7	5.5	C1-D09-32
R1-D-09314	7 ~ 10	2.2	4	4	4	7.5	C1-D09-32
R1-D-12316	10 ~ 13	3	5.5	5.5	5.5	10	C1-D09-32
R1-D-16321	13 ~ 18	4	7.5	9	9	15	C1-D09-32
R1-D-25322	18 ~ 25	5.5	11	11	11	18.5	C1-D09-32
R1-D-40353	23 ~ 32	7.5	15	15	15	22	C1-D40, D50, D65
R1-D-40355	30 ~ 40	10	18.5	22	22	30	C1-D40, D50, D65
R1-D-63357	38 ~ 50	11	22	25	25	37	C1-D40, D50, D65
R1-D-63359	48 ~ 57	15	25	30	30	45	C1-D40, D50, D65
R1-D-63361	57 ~ 66	18.5	30	37	37	55	C1-D40, D50, D65
R1-D-80363	63 ~ 80	22	33 ~ 37	40 ~ 45	40 ~ 45	59 ~ 63	C1-D80, D95