



Item No:YQK-70

crimping range: 4–70mm²
 crimping force: 8T
 crimping type: hexagon crimping
 stroke: 10mm
 length: approx.310mm
 weight: approx.2.80kg
 package: plastic box
 weight of box: approx. 0.56 kg

Accessories:

crimping dies: 4, 6, 8, 10, 16, 25, 35, 50, 70mm²
 Sealing O-ring: one set



Item No:YYQ-120

crimping range: 10–120mm²
 crimping force: 12T
 crimping type: hexagon crimping
 stroke: 14mm
 length: approx.425mm
 weight: approx.4.00kg
 package: plastic box
 weight of box: approx.0.77kg

Accessories:

crimping dies: 10, 16, 25, 35, 50, 70, 95, 120mm²
 Sealing O-ring: one set



Item No:YYQ-120A

crimping range: 10–120mm²
 crimping force: 12T
 crimping type: hexagon crimping
 stroke: 14mm
 length: approx.425mm
 weight: approx.4.20kg
 package: plastic box
 weight of box: approx. 0.81kg

Accessories:

crimping dies: 10, 16, 25, 35, 50, 70, 95, 120mm²
 Sealing O-ring: one set



Item No:YQK-240

crimping range: 16–240mm²
 crimping force: 16T
 crimping type: hexagon crimping
 stroke: 22mm
 length: approx.480mm
 weight: approx.5.20kg
 package: plastic box
 weight of box: approx. 1.20kg

Accessories:

crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240mm²
 Sealing O-ring: one set



Item No:YQK-300

crimping range: 16–300mm²
 crimping force: 16T
 crimping type: hexagon crimping
 stroke: 22mm
 length: approx.500mm
 weight: approx.6.30kg
 package: plastic box
 weight of box: approx.1.21kg

Accessories:

crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm²
 Sealing O-ring: one set

Head design.
Flip top style closed crimping head. Rotates 360



Item No: HT-300

for interchangeable dies.
Flip top style closed crimping head, rotates 360°
Automatic retraction when crimp is complete
Manual retraction in case of need.

Crimping range: 16–300mm²
crimping force: 60KN
crimping type: hexagon crimping
stroke: 17mm
length: approx. 460mm
weight: approx. 3.30kg
package: steel case

Accessories:
crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm²

Hand-load button

Relax during press
Quick restoration

High tensile aluminum alloy
Handiness

Prevent-slip handle



Item No: KYQ-300 safety system inside

crimping range: 16–300mm²
crimping force: 16T
crimping type: hexagon crimping
stroke: 22mm
length: approx. 500mm
weight: approx. 6.80kg
package: steel case
weight of case: approx. 3.30kg

Accessories:
crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm²



Item No: KYQ-300B safety system inside

crimping range: 16–300mm²
crimping force: 16T
crimping type: hexagon crimping
stroke: 22mm
length: approx. 500mm
weight: approx. 6.80kg
package: steel case
weight of case: approx. 3.30kg

Accessories:
crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm²



Item No:KYQ-300C safety system inside
 crimping range: 16–300mm²
 crimping force: 16T
 crimping type: hexagon crimping
 stroke: 20mm
 length: approx.500mm, weight: approx.6.80kg
 package: steel case
 weight of case: approx. 3.30kg
Accessories:
 crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300mm²



Item No:KYQ-400 safety system inside
 crimping range: 50–400mm²
 crimping force: 20T
 crimping type: hexagon crimping
 stroke: 25mm
 length: approx.540mm, weight: approx.8.30kg
 package: plastic box or steel case
 weight of case: approx. 4.00kg
Accessories:
 crimping dies: 50, 70, 95, 120, 150, 185, 240, 300, 400mm²



Item No:KDG-150 safety system inside
 open crimping head, rotate the die to choose crimping size.
 crimping range: 16–150mm²
 crimping force: 16T
 crimping type: indent crimping
 stroke: 20mm
 length: approx.500mm, weight: approx.4.60kg
 package: steel case
 weight of case: approx. 3.00kg
Accessories:
 Female dies: 16, 25, 35, 50, 70, 95, 120, 150 mm²
 Male dies: 16–25–35, 50–70–95, 120–150mm²



Item No:KDG-200
 open crimping head, rotate the die to choose crimping size.
 crimping range: 16–200mm²
 crimping force: 16T
 crimping type: indent crimping
 stroke: 20mm
 length: approx.510mm, weight: approx.4.90kg
 package: steel case
 weight of case: approx. 3.00kg
Accessories:
 Female dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 200 mm²
 Male dies: 16–25–35, 50–70–95, 120–150, 185–200mm²



Item No:KDG-150A
 open crimping head, rotate the die to choose crimping size.
 crimping range: 16–150 mm²
 crimping force: 16T
 crimping type: indent crimping
 stroke: 20mm
 length: approx.470mm
 weight: approx.3.50kg
 package: steel case
 weight of case: approx. 3.00kg
Accessories:
 Female dies: 16, 25, 35, 50, 70, 95, 120, 150 mm²
 Male dies: 16–25–35, 50–70–95, 120–150mm²



Item No:KDG-200A
 open crimping head, rotate the die to choose crimping size.
 crimping range: 16–200mm²
 crimping force: 16T
 crimping type: indent crimping
 stroke: 20mm
 length: approx.470mm, weight: approx.4.90kg
 package: steel case
 weight of case: approx. 3.00kg
Accessories:
 Female dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 200 mm²
 Male dies: 16–25–35, 50–70–95, 120–150, 185–200mm²

HAND HYDRAULIC COMPRESSION TOOL

- ※Design to accommodate hexagonal dies for applying compression fittings to copper, aluminum conductors.
- ※Two stage pumping action for rapid ram advance to the connector hold position with minimum pumping action.
- ※Automatic retraction when the pressure reaches 700kg/cm² (12T) reached.
- ※The glass fiber operation insulates the stick, can bear the electric voltage 200KV, keeping on the minute.
- ※180. rotatable head.
- ※The pressure outside the body adjusts to press the valve, don't need the whole structure to lie down.



Item No:CYO-410

safety system inside
 crimping force: 13T
 crimping range: 250mm² max. Copper conductor size
 stroke: 30mm
 oil capacity: 145cc
 weight: approx. 6.20kg
 package: plastic box
 weight of box: 1.80kg
 Accessories:
 crimping dies: 50, 70, 95, 120, 150, 185, 240, 300,400mm²



HYDRAULIC Crimping Tool



Item No:CYO-430

safety system inside
 crimping force: 13T
 crimping range: 250mm² max. Copper conductor size
 stroke: 30mm
 oil capacity: 145cc
 weight: approx. 6.40kg
 package: plastic box
 weight of box: 1.80kg
Accessories:
 crimping dies: 35, 50, 70, 95, 120, 150, 185, 240, 300,400mm²



Item No:CYO-510B

safety system inside
 crimping force: 13T
 crimping range: 380mm² max. Copper conductor size
 stroke: 38mm
 oil capacity: 200cc
 weight: approx. 7.80kg
 package: plastic box
 weight of box: 1.80kg
Accessories:
 crimping dies: 50, 70, 95, 120, 150, 185, 240, 300,400mm²



Item No: FYQ-300

crimping Range: 16-300 mm²
 crimping force: 20T
 crimping type: hexagon crimping
 Stroke: 22mm
 Weight approx. 11kg
 Package: steel case
 Weight of case: approx. 4.45kg
Accessories:
 crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300 mm²

HYDRAULIC CRIMPING TOOL

Item No: FYQ-300C

crimping range: 16-300 mm²
 crimping force: 20T
 crimping type: hexagon crimping
 Stroke: 22mm
 Weight approx: 11.50kg
 Package: steel case
 Weight of case: approx. 4.45kgs
Accessories:
 crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300 mm²



Item No: FYQ-400

crimping range: 16-400 mm²
 crimping force: 22T
 crimping type: hexagon crimping
 Stroke: 22mm
 Max Pressure: 22T
 Weight approx: 14.50kg
 Package: steel case
 Weight of case: approx. 4.50kgs
Accessories:
 crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400 mm²



Item No: CO-400B

crimping range: 16-400 mm²
 crimping force: 20T
 crimping type: hexagon crimping
 stroke: 22mm
 height: approx. 240mm, weight: approx. 6.50kg
 package: plastic box
 weight of box: approx. 1.00kgs
Accessories:
 crimping dies: 16, 25, 35, 50, 70, 95, 120, 150, 185, 240, 300, 400mm²
 Note: it can match hand pump CP-700.
 Catalogue page:

FUNCTION

- ※It is suitable for outside and inside project of the distributor house, it is the special tools for all kinds of connecting and building over head cable.
- ※It pressed tightly on 10KV-500KV high voltage cable casing pipe, cable clips naked ends and hexagon shape.
- ※We will develop the titanium alloy material to decrease the work deal.
- ※Welcome to order special specification tools.



Item No: FYQ-630

crimping range: 150-630 mm²
 crimping force: 30T
 crimping type: hexagon crimping
 stroke: 25mm
 height: approx. 350mm
 weight: approx. 16.00kgs
 package: steel case
 weight of case: approx. 8.80kgs

Accessories:

crimping dies: 150, 185, 240, 300, 400, 500, 630 mm²
 Note: it can match hand pump CP-700.
 Catalogue page:



Item No: FYQ-630A

crimping range: 150-630 mm²
 crimping force: 30T
 crimping type: hexagon crimping
 Stroke: 25mm
 height: approx. 370mm
 Weight approx: 17.60kg
 Package: steel case
 Weight of case: approx. 4.30kgs

Accessories:

crimping dies: 150, 185, 240, 300, 400, 500, 630 mm²
 Note: it can match hand pump CP-700 or electric pump ZCB6-5.
 Catalogue page.



Item No: FYQ-1000

crimping range: 400-1000 mm²
 crimping force: 55T
 crimping type: hexagon crimping
 Stroke: 28mm
 height: approx. 380mm
 Weight approx: 32.20kg
 Package: steel case
 Weight of case: approx. 5.50kgs

Accessories:

Press-joint dies: 400, 500, 630, 800, 1000 mm²
 Note: it suggest to match electric pump ZCB6-5
 Catalogue page



Item No: FHT-300

crimping Range: 16-300 mm² Cu-conductors,
 10-240 mm² Al-conductors
 crimping force: 6T
 crimping type: hexagon crimping
 Stroke: 16mm
 Weight approx. 4.00kg

Accessories:

crimping dies: 16, 25, 35, 50, 70, 95, 120, 150,
 185, 240, 300 mm²



Item No: SHP-430H

crimping range: 50-400 mm²
 crimping force: 13T
 crimping type: hexagon crimping
 stroke: 30mm
 height: approx. 240mm
 weight: approx. 6.50kg
 package: steel case

Accessories:

crimping dies: 50, 70, 95, 120, 150, 185,
 240, 300, 400mm²
 Note: it can match hand pump CP-700.



Item No: CYO-510H

crimping range: 50-400 mm²
 crimping force: 13T
 crimping type: hexagon crimping
 stroke: approx. 38mm
 height: approx. 370mm
 weight: approx. 5.70kg
 package: steel case

Accessories:

crimping dies: 50, 70, 95, 120, 150, 185,
 240, 300, 400 mm².