



METAL RING






ECONOMIC TYPE

1. The most peculiarity of this series of push buttons is to avail up-to-date design, Common Contact, by which makes this series economy buy value in money, compared with any other of panel push buttons.
2. This series simplify on-the-job assembly owing to the special design.

SPECIFICATIONS AND RATINGS

Rated voltage and current	AC	125V AC	250V AC	600V AC
		10A	6A	2A
	DC	110V DC	220V DC	600V DC
2 A		1.1A	0.4A	
Rated Insulation Voltage	600V AC, DC			

Operation frequency	1,200 operations/h
Life expectancy	Mechanical: 5,000,000 operations
	Electrical: 500,000 operations
Ambient temperature	-20 to +50°C (No freeze allowed)

PICTURE & DESCRIPTION	COLOR	ITEM NUMBER				
		1A	1B	1A1B	2A2B	
 FLAT PUSHBUTTON	●	φ25	FPB-2510	FPB-2501	FPB-2511	FPB-2522
	●	φ30	FPB-3010	FPB-3001	FPB-3011	FPB-3022
 MUSHROOM HEAD PUSHBUTTON	●	φ25	MPB-2510	MPB-2501	MPB-2511	MPB-2522
	●	φ30	MPB-3010	MPB-3001	MPB-3011	MPB-3022
 PUSH-LOCKED PUSHBUTTON	●	φ25	LMB-2510	LMB-2501	LMB-2511	LMB-2522
	●	φ30	LMB-3010	LMB-3001	LMB-3011	LMB-3022
 ILLUMINATED PUSHBUTTON DIRECT TYPE AC220V E-10 NEON BULB	●	φ25	IDS-2510	IDS-2501	IDS-2511	
	●	φ30	IDS-3010	IDS-3001	IDS-3011	
 ILLUMINATED PUSHBUTTON WITH TRANSFORMER ACV: 110, 220, 380, 440 E-10 FILAMENT BULB	●	φ25	ITS-2510	ITS-2501	ITS-2511	
	●	φ30	ITS-3010	ITS-3001	ITS-3011	