



DIGITAL MULTIMETER



DM 6266
3 ½ digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	1000V	±(0.8%+2)
AC Voltage	750V	±(1.2%+4)
AC Current	200A/1000A	±(3.0%+5)
Resistance	200 Ω/20k Ω	±(1.0%+1)
Continuity buzzer		✓
Low battery buzzer		✓
Hold	Data hold	
Input impedance	10M Ω	
Sampling rate	3 times/s	
AC Frequency response	(50-60)Hz	
Operation way	Manual range	
Max.Display	1999	
Clamp size	50mm	
Power	9V(6FF2)	
Product net weight	Approx:330g	
Standard Quantity Per Carton	30pcs/ctn	
Carton size	465×317×506mm	
Standard Gross Weight	Approx:26kg	



DM 6052+
3 ½ digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	20V/1000V	±(0.5%±5)
AC Voltage	700V	±(1%±5)
AC Current	20A/200A/2000A	±(1.9%±5)
Resistance	2k Ω	±(0.8%±5)
Diode		✓
Continuity buzzer		✓
Low battery buzzer		✓
Hold	Reading/Max. value hold	
Peak value measurement		✓
Panel calibrated		✓
Function protection		✓
Auto cathode show		✓
Backlight		✓
Input impedance	10M Ω	
Sampling rate	3 times/s	
AC Frequency response	(50-60)Hz	
Operation way	Manual range	
Max.Display	1999	
Clamp size	55mm	
Power	9V(6FF2)	
Product net weight	Approx:500g	
Standard Quantity Per Carton	25pcs	
Carton size	465×317×506mm	
Standard Gross Weight	Approx:30kg	



VC 830M
3 ½ digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	200mV/2000mV/20V/200V/600V	±(0.8%+10)
AC Voltage	200V/450V	±(1.5%+10)
DC Current	20uA/200uA/2000uA/20mA/200mA	±(1.5%+8)
Resistance	200 Ω/2000 Ω/20k Ω/200k Ω/2000k Ω	±(1.2%+8)
Diode test / Continuity buzzer		✓
Low battery indication		✓
Input impedance	10M Ω	
Sampling rate	3 times/s	
AC Frequency response	(40-400)Hz	
Operation way	Manual range	
Max.Display	1999	
LCD size	57×33mm	
Battery	3V(1.5V×2)	
Product net weight	Approx:180g	
Product dimension	145×80×28mm	
Standard Quantity Per Carton	60PCS	
Carton size	470×325×350mm	
Standard Gross Weight	Approx:20kg	



DIGITAL MULTIMETER



81B
3 1/2 digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	200mV/2V/20V/200V/600V	±(0.5%+4)
AC Voltage	200mV/2V/20V/200V/600V	±(0.8%+6)
DC Current	200uA/2000uA/20mA/200mA/10A	±(1.0%+10)
AC Current	200uA/2000uA/20mA/200mA/10A	±(1.5%+10)
Resistance	200Ω/2kΩ/20kΩ/200kΩ/2MΩ/20MΩ	±(0.8%+4)
Frequency	1Hz/10Hz/100Hz/1kHz/10kHz/100kHz/30MHz	±(1.0%+5)
Fahrenheit	(0-1832)°F	±(1.0%+5)
Diode test&Continuity buzzer		✓
Low battery indication		✓
Data hold		✓
Auto power off		✓
Function protection		✓
10A fuse		✓
Shock proof protection		✓
Self-resume fuse protection for mA		✓
Unit symbol display		✓
Max. Value measurement		✓
Input impedance	10MΩ	
Sampling rate	3 time/s	
AC Frequency response	(40-400)Hz	
Operation way	Auto/Manual range	
Max. Display	1999	
LCD size	57×33mm	
Battery	3V(1.5×2)	
Product Net Weight	Approx:200g(including battery)	
Product dimension	145×80×30mm	
Standard Quantity Per Carton	60PCS	
Carton size	470×325×35mm	
Standard Gross Weight	Approx:20kg	



70C
3 1/2 digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	600mV/6V/60V/600V/1000V	±(0.5%+4)
AC Voltage	600mV/6V/60V/600V/750V	±(0.8%+10)
DC Current	60mA/600mA/10A	±(1.0%+10)
AC Current	60mA/600mA/10A	±(1.5%+10)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+4)
Capacitance	40nF/400nF/4uF/40uF/200uF	±(3.5%+8)
Frequency	100Hz/1000Hz/10kHz/100kHz/1MHz/20MHz	±(0.3%+2)
Celsius	(-20-1000)°C	±(1.0%+5)
Fahrenheit	(0-1832)°F	±(1.5%+15)
USB interface jack		✓
Backlight		✓
61 section analog bar graph display	30times/second	
Key-press operation		✓
Misoperation protection		✓
Diode test & Continuity buzzer		✓
Low battery indication		✓
Data Hold		✓
Auto power off/Shock proof protection		✓
mA/10A fuse protection		✓
Unit symbol display		✓
Max. value measurement		✓
Relative value measurement		✓
Duty cycle measurement	0.1%-99.9%	
Input impedance	10MΩ	
Sampling rate	3time/s	
AC Frequency response	(40-400)Hz	
Max. Display	5999 (3 5/8)	
LCD size	68×47mm	
Battery	3V(1.5V×2)	
Product Net Weight	Approx: 320g(contain battery)	
Product dimension	200×90×45mm	
Carton size	465×375×66mm	
Standard Quantity Per Carton	30PCS	
Standard Gross Weight	23kg	



VC890C+
3 1/2 digits Lcd

SPECIFICATIONS:

Basic Function	Range	Accuracy
DC Voltage	200mV/2V/20V/200V	±(0.5%+3)
AC Voltage	1000V	±(0.8%+10)
AC Voltage	2V/20V/200V	±(0.8%+5)
AC Voltage	750V	±(1.2%+10)
DC Current	200uA/20mA	±(0.8%+10)
DC Current	200mA	±(1.2%+8)
DC Current	20A	±(2.0%+5)
AC Current	20mA	±(1.0%+15)
AC Current	200mA	±(2.0%+5)
AC Current	20A	±(3.0%+10)
Resistance	200Ω	±(0.8%+5)
Resistance	2kΩ/20kΩ/200kΩ	±(0.8%+3)
Resistance	20MΩ	±(1.0%+25)
Capacitance	20nF/2uF	±(2.5%+20)
Capacitance	200uF	±(5.0%+10)
Celsius	(-20-1000)°C	±400°C ±(1.0%+5)
Celsius		±400°C ±(1.5%+15)
Diode/Transistor		✓
Continuity buzzer		✓
Low battery indication		✓
Data hold		✓
Auto power off		✓
Backlight		✓
Function protection		✓
200mA protection		✓
Restorable Fuse protection		✓
Input impedance	10MΩ	
Sampling rate	3 time/s	
AC Frequency response	(40-400)Hz	
Operation way	Manual range	
Max. Display	1999	
LCD size	61×36mm	
Battery	9V(6F22)	
Product Net Weight	Approx:400g	
Product dimension	175×93×55mm	
Standard Quantity Per Carton	30PCS	
Carton size	405×350×450mm	
Standard Gross Weight	Approx:21kg	