

MODEL NO.	MEASUREMENT	MEASUREMENT RANGE	MOVEMENT	SCALES
CP-96 CP-72 CP-48	VOLTMETERS	DC 3, 5, 7.5, 10, 15, 20, 30, 50, 75, 100, 150, 200, 250, 300, 450, 500, 600V	Moving Coil	90°
		AC 30, 50, 75, 100, 120, 150, 200, 250, 300, 400, 450, 500, 600V	Moving Iron	
CP-96 CP-72 ★ CP-48 ( POINTER TYPE ONLY)	FREQUENCIES METER LINE SUPPLY 110V, 220V, 380V, 440V AC	POINTER TYPE 45~55Hz, 55~65Hz 45 - 65Hz	Moving Coil	
		REED TYPE CP-96 11 REED 45-55Hz 55-65Hz CP-72 7 REED 47-53Hz 57-63Hz		
CW-96 CW-72	AMMETERS	AC Direct : 0.1, 0.5, 1, 1.5, 3, 5, 7.5, 10, 15, 20, 30A Above 30A with separate external current transformer which secondary current is 5A	Moving Coil	240°
		DC Direct : 1,3,5,10,15,20,30,50,75, 100,150,200,250,300,500mA 1,3,5,7.5,10,20,30,50A Above 50A with separate external shunt(50 or 75mv)		
	VOLTMETERS	DC 3, 5, 7.5, 10, 15, 20, 30, 50, 75, 100, 150, 200, 250, 300, 450, 500, 600V		
		AC 30, 50, 75, 100, 120, 150 200, 250, 300, 400, 450, 500, 600V		
	FREQUENCIES METER LINE SUPPLY 110V, 220V, 380V 440V AC	POINTER TYPE 45~65HZ		
CP-96 CP-72 CW-96 CW-72	POWER FACTOR METERS	3 PHASE 3 WIRE BALANCED LINE LINE SUPPLY : 5A L-L : AC 220V, 380V, 415V, 440V 3 PHASE 4 WIRE (wattmeter only)	Moving Coil	CP-96 90° CP-72 90°
	WATTMETERS			CW-96 240° CW-72 240°

★ CP-96 AND CP-72 DOUBLE FREQUENCY METER REED TYPE AVAILABLE.