

## SSR 固態繼電器

輸入 Input Circuit		輸出 Output Circuit				外型 (Package NO.)			
電壓 Voltage Range	電流 Current	電壓範圍 Voltage Range	最大電流 Current	規格/型號 Model Number					
				零位觸發型 Zero Voltage Switching	隨機觸發型 Random Switching				
4-32VDC	8-10mA(DC)	70-240VAC	2A	SS2402DZ	X	1			
			3A	SS2403DZ	X	1			
			10A	SS2410DZ	SS2410DZ	2			
			15A	SS2415DZ	SS2415DZ	2			
			20A	SS2420DZ	SS2420DZ	2			
			25A	SS2425DZ	SS2425DZ	2			
			40A	SS2440DZ	SS2440DZ	2			
			60-75A	SS2460DZS-2475DZS	X	2			
			60A	SS2460DZ	X	3			
		75A	SS2475DZ	X	3				
		70-480VAC	10A	SS2410DZ	X	2			
			25A	SS2425DZ	X	2			
			40A	SS2440DZ	X	2			
			60-75A	SS4860DZS-4875DZS	X	2			
			65A	SS4865DZ	X	3			
		75A	SS4875DZ	X	3				
70-240VAC	2-5mA(AC)	70-240AC	10A	SS2410A	X	2			
			15A	SS2415A	X	2			
			20A	SS2420A	X	2			
			25A	SS2425A	X	2			
			40A	SS2440A	X	2			
70-480VAC	2-5mA(AC)	70-480VAC	40A	SS4840A	X	2			
			4-32VDC	8-10mA(DC)	3-60VDC	3A-25A	X	SD0603 SD0610 SD0625 OUTPUT:SCR	2
						10A-60A	X	MD0610-MD0640 OUTPUT:MOSFET	2
3-150VDC	10A	X	SD1510	2					

## 相位控制器 PHASE CONTROLLER

輸入 Input Circuit		輸出 Output Circuit		規格/型號 Model Number	外型 (Package NO.)
輸入電阻 Input Resistor	電壓範圍 VoltagRange	最大電流 Current			
100K-ohms Varistor  (500K-ohms Varistor)	70-240VAC	10A	SP2410	2	
		15A	SP2415	2	
		20A	SP2420	2	
		25A	SP2425	2	
		40A	SP2440	2	

Package 3



57.5x46.3x26.7(mm)

Package 2



57x43.6x23.3(mm)

Package 1



35x14.2x22.2(mm)